



Film viewing unit

Film viewing unit CRYSTAL - VIEW Professional Vario Plus

3 fluorescent tubes per panel, with separate panel switching, with nylon thread
electr. ballasts dimmable, power supply: 220 / 240 V AC 50 / 60 HZ
1 panel = 35 cm, 1 ON / OFF mainswitch for each unit, 1 DIMMER per panel,
fuses: 2 x 6,3 A, luminance: max. 2800 cd/m², color temp.: 6400 K

	Cat. No.	viewing area l x h (cm)	outer dim. l x h x d (mm)	fluorescent tubes	current cons. (A)	weight (kg)
	0330357	35 x 43	380 x 500 x 90	3 x 15 W	0,22	5,70
	0330707	70 x 43	725 x 500 x 90	6 x 15 W	0,42	9,00
	0331057	105 x 43	1075 x 500 x 90	9 x 15 W	0,61	13,50
	0331407	140 x 43	1424 x 500 x 90	12 x 15 W	0,92	16,50
	0331757	175 x 43	1775 x 500 x 90	15 x 15 W	1,10	19,50
	0332057	2 x 105 x 43	2 x 1075 x 960 x 90	2 x 9 x 15 W	1,22	29,00
	0332407	2 x 140 x 43	2 x 1425 x 960 x 90	2 x 12 x 15 W	1,78	34,00
Without picture						