

Film viewing unit with shutters

Film viewing unit with shutters

- 4 freely moving shutters for glare-free film reading, infinitely variable adjustment of luminance within the range from 10 to 100%, X-ray film viewer with high frequency converters, very quick ignition of fluorescent lamps, no flickering effect energy saving up to 25%, tiltable and removable front cover for cleaning and service jobs
- metal housing with white powder coating RAL 9002
- daylight tubes appr. 6.500 °K, luminance: 4.500 cd/m²
- excellent uniformity of the luminous density
- Voltage: 230 V, 50 Hz



Viewing area: 40 x 43 cm
outer dimm.: 660 x 690 x 120 mm
Power consumption: 70 VA
fluorescent tubes: 4 x 15 W
Weight: 23 kg
100404



Viewing area: 80 x 43 cm
outer dimm.: 1060 x 690 x 120 mm
Power consumption: 140 VA
fluorescent tubes: 4 x 30 W
Weight: 41 kg
100804



Viewing area: 105 x 43 cm
outer dimm.: 1380 x 690 x 120 mm
Power consumption: 170 VA
fluorescent tubes: 4 x 36 W
Weight: 49 kg
101054



Viewing area: 140 x 43 cm
outer dimm.: 1700 x 690 x 120 mm
Power consumption: 260 VA
fluorescent tubes: 4 x 58 W
Weight: 57 kg
101404